

LED LIGHT HEAD

Features

- Operate Voltage 10~30VDC
- 13 Flash Patterns

Operating Instruction

- Connect **RED** wire to +VDC – Fuse @2A.
- Connect **BLACK** wire to chassis ground.
- Connect **BLUE** wire to **BLACK** wire momentarily to select next flash pattern.
- Connect **BLUE** wire to **BLACK** wire for greater than 5 sec. to turn off the unit.

Synchronised Flash

Connect **YELLOW** wires of all units together and set all units to the synchronised pattern.

Alternate Flash

Connect **YELLOW** wires of all units together and set all units to either phase 1 or phase 2 of that alternate pattern. Units set on phase 1 will alternate with units set on phase 2.

Flash Patterns:

PA1	ECE R65 120FPM Single Flash P1
PA2	ECE R65 120FPM Single Flash P2
PA3	ECE R65 120FPM Double Flash P1
PA4	ECE R65 120FPM Double Flash P2
PA5	ECE R65 120FPM Quad Flash P1
PA6	ECE R65 120FPM Quad Flash P2
PA7	Single Flash 75 (SIM) P1
PA8	Single Flash 75 (SIM) P2
PA9	Double Flash 75 (SIM) P1
PA10	Double Flash 75 (SIM) P2
PA11	Quad Flash 75 (SIM) P1
PA12	Quad Flash 75 (SIM) P2
PA13	Steady
PA14	Off